


MC 系列连接器 MC Terminal Blocks


3.5mm间距 Pitch: 3.5mm

产品信息Product Information			产品信息Product Information			订货号/通道数 Order / Poles No.		附件Accessory
IEC/UL数据 IEC/UL Data	IEC	UL	锁线螺钉 Locking crew	-	-	MC-DRD3.5HXXP	4-20	
额定电流 Rated current	[A]	8	扭矩 Torque	[N·m]	-	MC-DRD3.5HXXP-K	4-20	
额定电压 Rated voltage	[V]	160	固定螺钉 Fixed screw	M2.5	-			
硬导线截面积 Solid	[mm²][AWG]	0.2-1.5	扭矩 Torque	[N·m]	0.3			
柔性导线截面积 Flexible	[mm²][AWG]	0.2-1.5	剥线长度 Strip length	[mm]	9-10			
额定冲击电压 Rated impulse voltage	[KV]	2.5						

MC-DRD3.5HXXP-0001




MC-DRD3.5HXXP-K-0001




3.5mm间距 Pitch: 3.5mm

产品信息Product Information				产品信息Product Information				订货号/通道数 Order /Poles No.		附件Accessory	
IEC/UL数据 IEC/UL Data		IEC	UL	锁线螺钉 Locking crew		-	MC-RF3.5HXXP-0001	2-24			
额定电流 Rated current		[A]	8	扭矩 Torque		[N·m]	-	MC-RF3.5HXXP-K-0001	2-24		
额定电压 Rated voltage		[V]	160	固定螺钉 Fixed screw		M2.5	-	MC-RF3.5HXXP-I-0001	2-24		
硬导线截面积 Solid		[mm²][AWG]	0.2-1.5	扭矩 Torque		[N·m]	0.3	MC-RF3.5HXXP-D-0001	2-24		
柔性导线截面积 Flexible		[mm²][AWG]	0.2-1.5	剥线长度 Strip length		[mm]	10				
额定冲击电压 Rated impulse voltage		[KV]	2.5								


MC-RF3.5HXXP-0001




MC-RF3.5HXXP-K-0001



MC-RF3.5HXXP-I-0001




MC-RF3.5HXXP-D-0001




3.5mm间距 Pitch: 3.5mm

产品信息Product Information			产品信息Product Information			订货号/通道数 Order /Poles No.		附件Accessory
IEC/UL数据 IEC/UL Data	IEC	UL	锁线螺钉 Locking crew	-	-	MC-DRF3.5HXXP-0001	2-24	
额定电流 Rated current	[A]	8	扭矩 Torque	[N·m]	-	MC-DRF3.5HXXP-D-0001	2-24	
额定电压 Rated voltage	[V]	160	固定螺钉 Fixed screw	-	-	MC-DRF3.5HXXP-K-0001	2-24	
硬导线截面积 Solid	[mm²][AWG]	0.2-1.5	扭矩 Torque	[N·m]	-			
柔性导线截面积 Flexible	[mm²][AWG]	0.2-1.5	剥线长度 Strip length	[mm]	10			
额定冲击电压 Rated impulse voltage	[KV]	2.5						


MC-DRF3.5HXXP-0001



MC-DRF3.5HXXP-D-0001




MC-DRF3.5HXXP-K-0001




3.5mm间距 Pitch: 3.5mm

产品信息Product Information				产品信息Product Information				订货号/通道数 Order /Poles No.		附件Accessory	
IEC/UL数据 IEC/UL Data				锁线螺钉 Locking crew		-		MC-DPAN3.5VXX-BK-2600		4-48	
额定电流 Rated current		[A]	8	扭矩 Torque		[N·m]	-	MC-DPAN3.5VXX-D-BK-2600		4-48	
额定电压 Rated voltage		[V]	160	固定螺钉 Fixed screw		M2.5	-	MC-DPAN3.5VXX-F-BK-2600		4-48	
硬导线截面积 Solid		[mm²][AWG]	-	扭矩 Torque		[N·m]	0.3	MC-DPAN3.5HXX-BK-2600		4-48	
柔性导线截面积 Flexible		[mm²][AWG]	-	剥线长度 Strip length		[mm]	-	MC-DPAN3.5HXX-D-BK-2600		4-48	
额定冲击电压 Rated impulse voltage		[KV]	2.5					MC-DPAN3.5HXX-F-BK-2600		4-48	


MC-DPAN3.5VXX-BK-2600




MC-DPAN3.5VXX-D-BK-2600




MC-DPAN3.5VXX-F-BK-2600



MC-DPAN3.5HXX-BK-2600



MC-DPAN3.5HXX-D-BK-2600



MC-DPAN3.5HXX-F-BK-2600

