



3.81mm间距 Pitch: 3.81mm

产品信息Product Information			产品信息Product Information			订货号/通道数 Order / Poles No.		附件Accessory	
IEC/UL数据 IEC/UL Data	IEC	UL	锁线螺钉 Locking crew	-	-	MC-RF3.81HXXP-0001	2-24	MC-JP3.81-X	
额定电流 Rated current	[A]	8	扭矩 Torque	[N·m]	-	MC-RF3.81HXXP-K-0001	2-24		
额定电压 Rated voltage	[V]	160	固定螺钉 Fixed screw	M2.5	-	MC-RF3.81HXXP-I-0001	2-24		
硬导线截面积 Solid	[mm²][AWG]	0.2-1.5	扭矩 Torque	[N·m]	0.3	MC-RF3.81HXXP-D-0001	2-24		
柔性导线截面积 Flexible	[mm²][AWG]	0.2-1.5	剥线长度 Strip length	[mm]	10				
额定冲击电压 Rated impulse voltage	[KV]	2.5							


MC-RF3.81HXXP-0001




MC-RF3.81HXXP-K-0001



MC-RF3.81HXXP-I-0001




MC-RF3.81HXXP-D-0001




3.81mm间距 Pitch: 3.81mm

产品信息Product Information			产品信息Product Information			订货号/通道数 Order / Poles No.		附件Accessory	
IEC/UL数据 IEC/UL Data	IEC	UL	锁线螺钉 Locking crew	-	-	MC-DPAN3.81VXX-BK-2600	4-48	MC-R-MSTB3.81	
额定电流 Rated current	[A]	8	扭矩 Torque	[N·m]	-	MC-DPAN3.81VXX-D-BK-2600	4-48		
额定电压 Rated voltage	[V]	160	固定螺钉 Fixed screw	M2.5	-	MC-DPAN3.81VXX-F-BK-2600	4-48		
硬导线截面积 Solid	[mm²][AWG]	-	扭矩 Torque	[N·m]	0.3	MC-DPAN3.81HXX-BK-2600	4-48		
柔性导线截面积 Flexible	[mm²][AWG]	-	剥线长度 Strip length	[mm]	-	MC-DPAN3.81HXX-D-BK-2600	4-48		
额定冲击电压 Rated impulse voltage	[KV]	2.5				MC-DPAN3.81HXX-F-BK-2600	4-48		


MC-DPAN3.81VXX-BK-2600




MC-DPAN3.81VXX-D-BK-2600




MC-DPAN3.81VXX-F-BK-2600




MC-DPAN3.81HXX-BK-2600



MC-DPAN3.81HXX-D-BK-2600




MC-DPAN3.81HXX-F-BK-2600




3.81mm间距 Pitch: 3.81mm

产品信息Product Information			产品信息Product Information			订货号/通道数 Order / Poles No.		附件Accessory	
IEC/UL数据 IEC/UL Data	IEC	UL	锁线螺钉 Locking crew	M2.5	-	MC-DRF3.81HXXP-0001	4-48		
额定电流 Rated current	[A]	8	扭矩 Torque	[N·m]	0.3	MC-DRF3.81HXXP-D-0001	4-48		
额定电压 Rated voltage	[V]	160	固定螺钉 Fixed screw	-	-	MC-DRF3.81HXXP-K-0001	4-48		
硬导线截面积 Solid	[mm²][AWG]	0.2-1.5	扭矩 Torque	[N·m]	-				
柔性导线截面积 Flexible	[mm²][AWG]	0.2-1.5	剥线长度 Strip length	[mm]	10				
额定冲击电压 Rated impulse voltage	[KV]	2.5							


MC-DRF3.81HXXP-0001



MC-DRF3.81HXXP-D-0001




MC-DRF3.81HXXP-K-0001




3.81mm间距 Pitch: 3.81mm

产品信息Product Information			产品信息Product Information			订货号/通道数 Order / Poles No.		附件Accessory	
IEC/UL数据 IEC/UL Data	IEC	UL	锁线螺钉 Locking crew	-	-	MC-RU3.81SHXX-0001	2-24		
额定电流 Rated current	[A]	8	扭矩 Torque	[N·m]	-	MC-RU3.81SHXX-F-0001	2-24		
额定电压 Rated voltage	[V]	160	固定螺钉 Fixed screw	M2.5	-	MC-RU3.81SVXX-0001	2-24		
硬导线截面积 Solid	[mm²][AWG]	0.2-1.5	扭矩 Torque	[N·m]	0.3	MC-RU3.81SVXX-F-0001	2-24		
柔性导线截面积 Flexible	[mm²][AWG]	0.2-1.5	剥线长度 Strip length	[mm]	-				
额定冲击电压 Rated impulse voltage	[KV]	2.5							


MC-RU3.81SHXX-0001



MC-RU3.81SHXX-F-0001



MC-RU3.81SVXX-0001



MC-RU3.81SVXX-F-0001

