



5.08mm间距 Pitch: 5.08mm

产品信息Product Information			产品信息Product Information			订货号/通道数 Order /Poles No.			附件Accessory		
IEC/UL数据 IEC/UL Data	IEC	UL	锁线螺钉 Locking crew	[N·m]	-	MC-PD5.08HXX-0001	2-24		MC-R-MSTB3.61		
额定电流 Rated current	[A]	8	扭矩 Torque	[N·m]	-	MC-PD5.08HXX-F-0001	2-24				
额定电压 Rated voltage	[V]	320	固定螺钉 Fixed screw		M2.5	MC-PD5.08HXX-I-0001	2-24				
硬导线截面积 Solid	[mm²][AWG]	-	扭矩 Torque	[N·m]	0.3	MC-PD5.08HXX-0001	2-24				
柔性导线截面积 Flexible	[mm²][AWG]	-	剥线长度 Strip length	[mm]	-	MC-PD5.08VXX-F-0001	2-24				
额定冲击电压 Rated impulse voltage	[KV]	4				MC-PD5.08VXX-I-0001	2-24				


MC-PD5.08HXX-0001




MC-PD5.08HXX-F-0001




MC-PD5.08HXX-I-0001




MC-PD5.08VXX-0001



MC-PD5.08VXX-F-0001




MC-PD5.08VXX-I-0001




5.08mm间距 Pitch: 5.08mm

产品信息Product Information			产品信息Product Information			订货号/通道数 Order /Poles No.			订货号/通道数 Order /Poles No.		
IEC/UL数据 IEC/UL Data	IEC	UL	锁线螺钉 Locking crew	[N·m]	-	MC-DPAB5.08HXX-0001	4-48		MC-DPAB5.08VXX-G-0001	4-48	
额定电流 Rated current	[A]	10	扭矩 Torque	[N·m]	-	MC-DPAB5.08HXX-F-0001	4-48		MC-DPAB5.08VXX-I-0001	4-48	
额定电压 Rated voltage	[V]	320	固定螺钉 Fixed screw		M2.5	MC-DPAB5.08HXX-G-0001	4-48				
硬导线截面积 Solid	[mm²][AWG]	-	扭矩 Torque	[N·m]	0.3	MC-DPAB5.08HXX-I-0001	4-48				
柔性导线截面积 Flexible	[mm²][AWG]	-	剥线长度 Strip length	[mm]	-	MC-DPAB5.08VXX-0001	4-48				
额定冲击电压 Rated impulse voltage	[KV]	4				MC-DPAB5.08VXX-F-0001	4-48				


MC-DPAB5.08HXX-0001




MC-DPAB5.08HXX-F-0001




MC-DPAB5.08HXX-G-0001



MC-DPAB5.08VXX-G-0001




MC-DPAB5.08VXX-I-0001




5.08mm间距 Pitch: 5.08mm

产品信息Product Information			产品信息Product Information			订货号/通道数 Order /Poles No.			附件Accessory		
IEC/UL数据 IEC/UL Data	IEC	UL	锁线螺钉 Locking crew	[N·m]	-	MC-DPA5.08HXX-0002	4-48		MC-P-MSTB-0001		
额定电流 Rated current	[A]	10	扭矩 Torque	[N·m]	-	MC-DPA5.08HXX-F-0002	4-48				
额定电压 Rated voltage	[V]	320	固定螺钉 Fixed screw		M2.5	MC-DPA5.08VXX-0002	4-48				
硬导线截面积 Solid	[mm²][AWG]	-	扭矩 Torque	[N·m]	0.3	MC-DPA5.08VXX-F-0002	4-48				
柔性导线截面积 Flexible	[mm²][AWG]	-	剥线长度 Strip length	[mm]	-						
额定冲击电压 Rated impulse voltage	[KV]	4									


MC-DPA5.08HXX-0002




MC-DPA5.08HXX-F-0002




MC-DPA5.08VXX-0002




MC-DPA5.08VXX-F-0002



MC-DPAB5.08HXX-I-0001



MC-DPAB5.08VXX-0001



MC-DPAB5.08VXX-F-0001

