





3.81mm间距 Pitch: 3.81mm		MC-DTM3.81HXXC-0001	
产品信息Product Information		产品信息Product Information	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M2
额定电流 Rated current [A]	8 10	扭矩 Torque [N·m]	0.2
额定电压 Rated voltage [V]	160 300	固定螺钉 Fixed screw	-
硬导线截面积 Solid [mm²][AWG]	0.2-1.5 24-16	扭矩 Torque [N·m]	-
柔性导线截面积 Flexible [mm²][AWG]	0.2-1.5 24-16	剥线长度 Strip length [mm]	5
额定冲击电压 Rated impulse voltage [KV]	2.5 -		
订货号/通道数 Order /Poles No.		附件Accessory	
MC-DTM3.81HXXC-0001		2-24	





3.81mm间距 Pitch: 3.81mm		MC-TTM3.81HXXC-0001	
产品信息Product Information		产品信息Product Information	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M2
额定电流 Rated current [A]	8 10	扭矩 Torque [N·m]	0.2
额定电压 Rated voltage [V]	160 300	固定螺钉 Fixed screw	-
硬导线截面积 Solid [mm²][AWG]	0.2-1.5 24-16	扭矩 Torque [N·m]	-
柔性导线截面积 Flexible [mm²][AWG]	0.2-1.5 24-16	剥线长度 Strip length [mm]	5
额定冲击电压 Rated impulse voltage [KV]	2.5 -		
订货号/通道数 Order /Poles No.		附件Accessory	
MC-TTM3.81HXXC-0001		2-24	




3.81mm间距 Pitch: 3.81mm		MC-TM3.81BXXC-0001	
产品信息Product Information		产品信息Product Information	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M2
额定电流 Rated current [A]	10 10	扭矩 Torque [N·m]	0.2
额定电压 Rated voltage [V]	200 300	固定螺钉 Fixed screw	-
硬导线截面积 Solid [mm²][AWG]	0.2-1.5 24-16	扭矩 Torque [N·m]	-
柔性导线截面积 Flexible [mm²][AWG]	0.2-1.0 24-16	剥线长度 Strip length [mm]	4-5
额定冲击电压 Rated impulse voltage [KV]	2.5 -		
订货号/通道数 Order /Poles No.		附件Accessory	
MC-TM3.81BXXC-0001		2P-12P	





3.81mm间距 Pitch: 3.81mm		MC-TE3.81HXXC-0001	
产品信息Product Information		产品信息Product Information	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M2
额定电流 Rated current [A]	12 12	扭矩 Torque [N·m]	0.2
额定电压 Rated voltage [V]	160 300	固定螺钉 Fixed screw	-
硬导线截面积 Solid [mm²][AWG]	0.2-1.5 24-16	扭矩 Torque [N·m]	-
柔性导线截面积 Flexible [mm²][AWG]	0.2-1.5 24-16	剥线长度 Strip length [mm]	5-6
额定冲击电压 Rated impulse voltage [KV]	2.5 -		
订货号/通道数 Order /Poles No.		附件Accessory	
MC-TE3.81HXXC-0001		2-24	







3.81mm间距 Pitch: 3.81mm		MC-TEH3.81HXXC-0001	
产品信息Product Information		产品信息Product Information	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M2
额定电流 Rated current [A]	12 12	扭矩 Torque [N·m]	0.2
额定电压 Rated voltage [V]	160 300	固定螺钉 Fixed screw	-
硬导线截面积 Solid [mm²][AWG]	0.2-1.5 24-16	扭矩 Torque [N·m]	-
柔性导线截面积 Flexible [mm²][AWG]	0.2-1.5 24-16	剥线长度 Strip length [mm]	5-6
额定冲击电压 Rated impulse voltage [KV]	2.5 -		
订货号/通道数 Order /Poles No.		附件Accessory	
MC-TEH3.81HXXC-0001		2-24	



3.81mm间距 Pitch: 3.81mm		MC-DTEH3.81HXXC-0001	
产品信息Product Information		产品信息Product Information	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M2
额定电流 Rated current [A]	12 12	扭矩 Torque [N·m]	0.2
额定电压 Rated voltage [V]	160 300	固定螺钉 Fixed screw	-
硬导线截面积 Solid [mm²][AWG]	0.2-1.5 24-16	扭矩 Torque [N·m]	-
柔性导线截面积 Flexible [mm²][AWG]	0.2-1.5 24-16	剥线长度 Strip length [mm]	5-6
额定冲击电压 Rated impulse voltage [KV]	2.5 -		
订货号/通道数 Order /Poles No.		附件Accessory	
MC-DTEH3.81HXXC-0001		2-24	



5.0mm间距 Pitch: 5.0mm		MC-TI5.0HXXP-BK-0001		MC-TI5.0HXXP-BK-1600	
产品信息Product Information		产品信息Product Information		订货号/通道数 Order /Poles No.	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	-	MC-TI5.0HXXP-BK-0001	2-24
额定电流 Rated current [A]	17.5 12	扭矩 Torque [N·m]	-	MC-TI5.0HXXP-BK-1600	2-24
额定电压 Rated voltage [V]	320 300	固定螺钉 Fixed screw	-	MC-TI5.0VXXP-BK-0001	2-24
硬导线截面积 Solid [mm²][AWG]	0.2-1.5 24-14	扭矩 Torque [N·m]	-	MC-TI5.0VXXP-BK-1600	2-24
柔性导线截面积 Flexible [mm²][AWG]	0.2-1.5 24-14	剥线长度 Strip length [mm]	8-9		
额定冲击电压 Rated impulse voltage [KV]	4 -				



5.0mm间距 Pitch: 5.0mm		MC-TI5.0HXXP-BK-0001-SMT		MC-TI5.0VXXP-BK-0001-SMT	
产品信息Product Information		产品信息Product Information		订货号/通道数 Order /Poles No.	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	-	MC-TI5.0HXXP-BK-0001-SMT	2-24
额定电流 Rated current [A]	17.5 12	扭矩 Torque [N·m]	-	MC-TI5.0VXXP-BK-0001-SMT	2-24
额定电压 Rated voltage [V]	320 300	固定螺钉 Fixed screw	-		
硬导线截面积 Solid [mm²][AWG]	0.2-1.5 24-16	扭矩 Torque [N·m]	-		
柔性导线截面积 Flexible [mm²][AWG]	0.2-1.5 24-16	剥线长度 Strip length [mm]	8-9		
额定冲击电压 Rated impulse voltage [KV]	4 -				

