




5.0mm间距 Pitch: 5.0mm		5.0mm间距 Pitch: 5.0mm
产品信息Product Information	产品信息Product Information	MC-TE5.0HXXC-0001
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew M3
额定电流 Rated current [A]	14 13.5	扭矩 Torque [N·m] 0.5
额定电压 Rated voltage [V]	320 300	固定螺钉 Fixed screw -
硬导线截面积 Solid [mm²][AWG]	0.2-1.5 24-16	扭矩 Torque [N·m] -
柔性导线截面积 Flexible [mm²][AWG]	0.2-1.5 24-16	剥线长度 Strip length [mm] 6-7
额定冲击电压 Rated impulse voltage [KV]	4 -	
订货号/通道数 Order /Poles No.	附件Accessory	
MC-TE5.0HXXC-0001	2-24	




5.0mm间距 Pitch: 5.0mm		5.0mm间距 Pitch: 5.0mm
产品信息Product Information	产品信息Product Information	MC-TEH5.0HXXC-0001
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew M3
额定电流 Rated current [A]	14 13.5	扭矩 Torque [N·m] 0.5
额定电压 Rated voltage [V]	320 300	固定螺钉 Fixed screw -
硬导线截面积 Solid [mm²][AWG]	0.2-1.5 30-16	扭矩 Torque [N·m] -
柔性导线截面积 Flexible [mm²][AWG]	0.2-1.5 30-16	剥线长度 Strip length [mm] 6-7
额定冲击电压 Rated impulse voltage [KV]	4 -	
订货号/通道数 Order /Poles No.	附件Accessory	
MC-TEH5.0HXXC-0001	2-24	




5.0mm间距 Pitch: 5.0mm		5.0mm间距 Pitch: 5.0mm
产品信息Product Information	产品信息Product Information	MC-DTE5.0HXXC-0001
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew M3
额定电流 Rated current [A]	14 13.5	扭矩 Torque [N·m] 0.5
额定电压 Rated voltage [V]	320 300	固定螺钉 Fixed screw -
硬导线截面积 Solid [mm²][AWG]	0.2-1.5 24-16	扭矩 Torque [N·m] -
柔性导线截面积 Flexible [mm²][AWG]	0.2-1.5 24-16	剥线长度 Strip length [mm] 6-7
额定冲击电压 Rated impulse voltage [KV]	4 -	
订货号/通道数 Order /Poles No.	附件Accessory	
MC-DTE5.0HXXC-0001	2-24	




5.0mm间距 Pitch: 5.0mm		5.0mm间距 Pitch: 5.0mm
产品信息Product Information	产品信息Product Information	MC-TD5.0HXXC-0001
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew M3
额定电流 Rated current [A]	24 15	扭矩 Torque [N·m] 0.5
额定电压 Rated voltage [V]	400 300	固定螺钉 Fixed screw -
硬导线截面积 Solid [mm²][AWG]	0.2-2.5 24-12	扭矩 Torque [N·m] -
柔性导线截面积 Flexible [mm²][AWG]	0.2-2.5 24-12	剥线长度 Strip length [mm] 7-8
额定冲击电压 Rated impulse voltage [KV]	4 -	
订货号/通道数 Order /Poles No.	附件Accessory	
MC-TD5.0HXXC-0001	2-24	




5.0mm间距 Pitch: 5.0mm		5.0mm间距 Pitch: 5.0mm
产品信息Product Information	产品信息Product Information	MC-TD5.0AXXC-0001
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew M3
额定电流 Rated current [A]	24 15	扭矩 Torque [N·m] 0.5
额定电压 Rated voltage [V]	400 300	固定螺钉 Fixed screw -
硬导线截面积 Solid [mm²][AWG]	0.2-2.5 24-12	扭矩 Torque [N·m] -
柔性导线截面积 Flexible [mm²][AWG]	0.2-2.5 24-12	剥线长度 Strip length [mm] 7-8
额定冲击电压 Rated impulse voltage [KV]	4 -	
订货号/通道数 Order /Poles No.	附件Accessory	
MC-TD5.0AXXC-0001	2-24	




5.0mm间距 Pitch: 5.0mm		5.0mm间距 Pitch: 5.0mm
产品信息Product Information	产品信息Product Information	MC-DTD5.0HXXC-0001
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew M3
额定电流 Rated current [A]	24 15	扭矩 Torque [N·m] 0.5
额定电压 Rated voltage [V]	400 300	固定螺钉 Fixed screw -
硬导线截面积 Solid [mm²][AWG]	0.2-2.5 24-12	扭矩 Torque [N·m] -
柔性导线截面积 Flexible [mm²][AWG]	0.2-2.5 24-12	剥线长度 Strip length [mm] 7-8
额定冲击电压 Rated impulse voltage [KV]	4 -	
订货号/通道数 Order /Poles No.	附件Accessory	
MC-DTD5.0HXXC-0001	4-48	




5.0mm间距 Pitch: 5.0mm		5.0mm间距 Pitch: 5.0mm
产品信息Product Information	产品信息Product Information	MC-TF5.0HXXC-0001
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew M3
额定电流 Rated current [A]	24 15	扭矩 Torque [N·m] 0.5
额定电压 Rated voltage [V]	400 300	固定螺钉 Fixed screw -
硬导线截面积 Solid [mm²][AWG]	0.2-2.5 24-12	扭矩 Torque [N·m] -
柔性导线截面积 Flexible [mm²][AWG]	0.2-2.5 24-12	剥线长度 Strip length [mm] 7-8
额定冲击电压 Rated impulse voltage [KV]	4 -	
订货号/通道数 Order /Poles No.	附件Accessory	
MC-TF5.0HXXC-0001	2-24	



5.0mm间距 Pitch: 5.0mm		5.0mm间距 Pitch: 5.0mm
产品信息Product Information	产品信息Product Information	MC-TF5.0AXXC-0001
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew M3
额定电流 Rated current [A]	24 15	扭矩 Torque [N·m] 0.5
额定电压 Rated voltage [V]	400 300	固定螺钉 Fixed screw -
硬导线截面积 Solid [mm²][AWG]	0.2-2.5 24-12	扭矩 Torque [N·m] -
柔性导线截面积 Flexible [mm²][AWG]	0.2-2.5 24-12	剥线长度 Strip length [mm] 7-8
额定冲击电压 Rated impulse voltage [KV]	4 -	
订货号/通道数 Order /Poles No.	附件Accessory	
MC-TF5.0AXXC-0001	2-24	



5.0mm间距 Pitch: 5.0mm		5.0mm间距 Pitch: 5.0mm
产品信息Product Information	产品信息Product Information	MC-DTF5.0HXXC-0001
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew M3
额定电流 Rated current [A]	24 15	扭矩 Torque [N·m] 0.5
额定电压 Rated voltage [V]	400 300	固定螺钉 Fixed screw -
硬导线截面积 Solid [mm²][AWG]	0.2-2.5 24-12	扭矩 Torque [N·m] -
柔性导线截面积 Flexible [mm²][AWG]	0.2-2.5 24-12	剥线长度 Strip length [mm] 7-8
额定冲击电压 Rated impulse voltage [KV]	4 -	
订货号/通道数 Order /Poles No.	附件Accessory	
MC-DTF5.0HXXC-0001	4-48	



5.0mm间距 Pitch: 5.0mm		5.0mm间距 Pitch: 5.0mm
产品信息Product Information	产品信息Product Information	MC-TCS.0VXXP-N-GY-0001
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew -
额定电流 Rated current [A]	24 20	扭矩 Torque [N·m] -
额定电压 Rated voltage [V]	320 300	固定螺钉 Fixed screw -
硬导线截面积 Solid [mm²][AWG]	0.2-2.5 24-12	扭矩 Torque [N·m] -
柔性导线截面积 Flexible [mm²][AWG]	0.2-1.5 24-12	剥线长度 Strip length [mm] 8-9
额定冲击电压 Rated impulse voltage [KV]	4 -	
订货号/通道数 Order /Poles No.	附件Accessory	
MC-TCS.0VXXP-N-GY-0001	1P-12P	

