




5.08mm间距 Pitch: 5.08mm

产品信息Product Information		产品信息Product Information	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M3
额定电流 Rated current	[A] 24 15	扭矩 Torque	[N·m] 0.5
额定电压 Rated voltage	[V] 320 300	固定螺钉 Fixed screw	-
硬导线截面积 Solid	[mm ²][AWG] 0.2-2.5 24-16	扭矩 Torque	[N·m] -
柔性导线截面积 Flexible	[mm ²][AWG] 0.2-1.5 24-16	剥线长度 Strip length	[mm] 6-7
额定冲击电压 Rated impulse voltage	[kV] 4 -		
订货号/通道数 Order /Poles No.		附件Accessory	
MC-DTE5.08HXXC-0001		2-24	




5.08mm间距 Pitch: 5.08mm

产品信息Product Information		产品信息Product Information	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M3
额定电流 Rated current	[A] 24 15	扭矩 Torque	[N·m] 0.5
额定电压 Rated voltage	[V] 400 300	固定螺钉 Fixed screw	-
硬导线截面积 Solid	[mm ²][AWG] 0.2-2.5 24-16	扭矩 Torque	[N·m] -
柔性导线截面积 Flexible	[mm ²][AWG] 0.2-2.5 24-16	剥线长度 Strip length	[mm] 7-8
额定冲击电压 Rated impulse voltage	[kV] 4 -		
订货号/通道数 Order /Poles No.		附件Accessory	
MC-TD5.08HXXC-0001		2-24	





5.08mm间距 Pitch: 5.08mm

产品信息Product Information		产品信息Product Information	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M3
额定电流 Rated current	[A] 24 15	扭矩 Torque	[N·m] 0.5
额定电压 Rated voltage	[V] 400 250	固定螺钉 Fixed screw	-
硬导线截面积 Solid	[mm ²][AWG] 0.2-2.5 24-12	扭矩 Torque	[N·m] -
柔性导线截面积 Flexible	[mm ²][AWG] 0.2-2.5 24-12	剥线长度 Strip length	[mm] 7-8
额定冲击电压 Rated impulse voltage	[kV] 4 -		
订货号/通道数 Order /Poles No.		附件Accessory	
MC-TD5.08AXXC-0001		2-24	




5.08mm间距 Pitch: 5.08mm

产品信息Product Information		产品信息Product Information	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M3
额定电流 Rated current	[A] 24 15	扭矩 Torque	[N·m] 0.5
额定电压 Rated voltage	[V] 400 300	固定螺钉 Fixed screw	-
硬导线截面积 Solid	[mm ²][AWG] 0.2-2.5 24-12	扭矩 Torque	[N·m] -
柔性导线截面积 Flexible	[mm ²][AWG] 0.2-2.5 24-12	剥线长度 Strip length	[mm] 7-8
额定冲击电压 Rated impulse voltage	[kV] 4 -		
订货号/通道数 Order /Poles No.		附件Accessory	
MC-DTD5.08HXXC-0001		2-24	




5.08mm间距 Pitch: 5.08mm

产品信息Product Information		产品信息Product Information	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M3
额定电流 Rated current	[A] 24 15	扭矩 Torque	[N·m] 0.5-0.6
额定电压 Rated voltage	[V] 400 300	固定螺钉 Fixed screw	-
硬导线截面积 Solid	[mm ²][AWG] 0.2-2.5 24-12	扭矩 Torque	[N·m] -
柔性导线截面积 Flexible	[mm ²][AWG] 0.2-2.5 24-12	剥线长度 Strip length	[mm] 7-8
额定冲击电压 Rated impulse voltage	[kV] 4 -		
订货号/通道数 Order /Poles No.		附件Accessory	
MC-TTD5.08HXXC-0001		6-72	




5.08mm间距 Pitch: 5.08mm

产品信息Product Information		产品信息Product Information	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M3
额定电流 Rated current	[A] 24 15	扭矩 Torque	[N·m] 0.5
额定电压 Rated voltage	[V] 400 300	固定螺钉 Fixed screw	-
硬导线截面积 Solid	[mm ²][AWG] 0.2-2.5 24-12	扭矩 Torque	[N·m] -
柔性导线截面积 Flexible	[mm ²][AWG] 0.2-2.5 24-12	剥线长度 Strip length	[mm] 7-8
额定冲击电压 Rated impulse voltage	[kV] 4 -		
订货号/通道数 Order /Poles No.		附件Accessory	
MC-TF5.08HXXC-0001		2-24	




5.08mm间距 Pitch: 5.08mm

产品信息Product Information		产品信息Product Information	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M3
额定电流 Rated current	[A] 24 20	扭矩 Torque	[N·m] 0.5
额定电压 Rated voltage	[V] 400 300	固定螺钉 Fixed screw	-
硬导线截面积 Solid	[mm ²][AWG] 0.2-2.5 24-12	扭矩 Torque	[N·m] -
柔性导线截面积 Flexible	[mm ²][AWG] 0.2-2.5 24-12	剥线长度 Strip length	[mm] 7-8
额定冲击电压 Rated impulse voltage	[kV] 4 -		
订货号/通道数 Order /Poles No.		附件Accessory	
MC-TF5.08AXXC-0001		2-24	




5.08mm间距 Pitch: 5.08mm

产品信息Product Information		产品信息Product Information	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M3
额定电流 Rated current	[A] 20 10	扭矩 Torque	[N·m] 0.5
额定电压 Rated voltage	[V] 400 250	固定螺钉 Fixed screw	-
硬导线截面积 Solid	[mm ²][AWG] 0.2-2.5 24-12	扭矩 Torque	[N·m] -
柔性导线截面积 Flexible	[mm ²][AWG] 0.2-2.5 24-12	剥线长度 Strip length	[mm] 10-11
额定冲击电压 Rated impulse voltage	[kV] 4 -		
订货号/通道数 Order /Poles No.		附件Accessory	
MC-TF5.08CXXC-0001		2-24	



5.08mm间距 Pitch: 5.08mm

产品信息Product Information		产品信息Product Information	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M3
额定电流 Rated current	[A] 24 15	扭矩 Torque	[N·m] 0.5
额定电压 Rated voltage	[V] 400 125	固定螺钉 Fixed screw	-
硬导线截面积 Solid	[mm ²][AWG] 0.2-2.5 24-12	扭矩 Torque	[N·m] -
柔性导线截面积 Flexible	[mm ²][AWG] 0.2-2.5 24-12	剥线长度 Strip length	[mm] 7-8
额定冲击电压 Rated impulse voltage	[kV] 4 -		
订货号/通道数 Order /Poles No.		附件Accessory	
MC-DTF5.08HXXC-0001		2-24	



5.08mm间距 Pitch: 5.08mm

产品信息Product Information		产品信息Product Information	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M3
额定电流 Rated current	[A] 24 15	扭矩 Torque	[N·m] 0.5-0.6
额定电压 Rated voltage	[V] 400 300	固定螺钉 Fixed screw	-
硬导线截面积 Solid	[mm ²][AWG] 0.2-2.5 24-12	扭矩 Torque	[N·m] -
柔性导线截面积 Flexible	[mm ²][AWG] 0.2-2.5 24-12	剥线长度 Strip length	[mm] 7-8
额定冲击电压 Rated impulse voltage	[kV] 4 -		
订货号/通道数 Order /Poles No.		附件Accessory	
MC-TTD5.08HXXC-0001		6P-72P	

