


9.52mm间距 Pitch: 9.52mm

产品信息Product Information		产品信息Product Information	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M3
额定电流 Rated current	[A] 32 30	扭矩 Torque	[N·m] 0.5
额定电压 Rated voltage	[V] 1000 600	固定螺钉 Fixed screw	-
硬导线截面积 Solid	[mm²][AWG] 0.2-6.0 24-10	扭矩 Torque	[N·m] -
柔性导线截面积 Flexible	[mm²][AWG] 0.2-6.0 24-10	剥线长度 Strip length	[mm] 8-9
额定冲击电压 Rated impulse voltage	[KV] 8 -		
订货号/通道数 Order /Poles No.		附件Accessory	
MC-TH/F9.52HXXC-0001		2P-12P	



MC-TH/F9.52HXXC-0001




10.16mm间距 Pitch: 10.16mm

产品信息Product Information		产品信息Product Information	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M4
额定电流 Rated current	[A] 57 65	扭矩 Torque	[N·m] 1.2
额定电压 Rated voltage	[V] 1000 300	固定螺钉 Fixed screw	-
硬导线截面积 Solid	[mm²][AWG] 0.5-16 20-6	扭矩 Torque	[N·m] -
柔性导线截面积 Flexible	[mm²][AWG] 0.5-16 20-6	剥线长度 Strip length	[mm] 11-12
额定冲击电压 Rated impulse voltage	[KV] 8 -		
订货号/通道数 Order /Poles No.		附件Accessory	
MC-TJ10.16HXXC-0001		2P-12P	




MC-TJ10.16HXXC-0001




10.16mm间距 Pitch: 10.16mm

产品信息Product Information		产品信息Product Information		订货号/通道数 Order /Poles No.		附件Accessory	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M4	MC-TH10.16HXXC-0001	2-12		
额定电流 Rated current	[A] 76 60	扭矩 Torque	[N·m] 1.2	MC-TH/B10.16H01C-0001	1		
额定电压 Rated voltage	[V] 1000 600	固定螺钉 Fixed screw	-	MC-TH/F10.16H01C-0001	1		
硬导线截面积 Solid	[mm²][AWG] 0.5-16 20-6	扭矩 Torque	[N·m] -				
柔性导线截面积 Flexible	[mm²][AWG] 0.5-16 20-6	剥线长度 Strip length	[mm] 10-12				
额定冲击电压 Rated impulse voltage	[KV] 8 -						


MC-TH10.16HXXC-0001



MC-TH/B10.16H01C-0001




MC-TH/F10.16H01C-0001




15.0mm间距 Pitch: 15.0mm

产品信息Product Information		产品信息Product Information		订货号/通道数 Order /Poles No.		附件Accessory	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M5	MC-TK15HXXC-0001	2-9		
额定电流 Rated current	[A] 125 115	扭矩 Torque	[N·m] 2.0	MC-TK15HXXC-B-0001	2-9		
额定电压 Rated voltage	[V] 1000 600	固定螺钉 Fixed screw	-	MC-TK15H01C-BL-0001	1		
硬导线截面积 Solid	[mm²][AWG] 0.5-35 20-2	扭矩 Torque	[N·m] -	MC-TK15H01C-BR-0001	1		
柔性导线截面积 Flexible	[mm²][AWG] 0.5-35 -	剥线长度 Strip length	[mm] 18-19				
额定冲击电压 Rated impulse voltage	[KV] 8 -						


MC-TK15HXXC-0001



MC-TK15HXXC-B-0001



MC-TK15H01C-BL-0001



MC-TK15H01C-BR-0001

