








235系列单孔PCB端子排 235 Series single hole PCB terminal block 间距 Pitch: 5.0mm

产品信息Product Information		订货号/通道数 Order /Poles No.	
IEC/UL数据 IEC/UL Data	IEC UL	2352XX/010	2-24
额定电流 Rated current [A]	17.5 10		
额定电压 Rated voltage [V]	320 300		
硬导线截面积 Solid [mm²][AWG]	0.2-2.5 24-14		
柔性导线截面积 Flexible [mm²][AWG]	0.2-2.5 24-14		
额定冲击电压 Rated impulse voltage [KV]	4.0 -		
锁线螺钉 Locking crew	-		
扭矩 Torque [N·m]	-		
固定螺钉 Fixed screw	-		
扭矩 Torque [N·m]	-		
剥线长度 Strip length [mm]	9-10		




235系列单孔PCB端子排 235 Series single hole PCB terminal block 间距 Pitch: 7.5mm

产品信息Product Information		订货号/通道数 Order /Poles No.	
IEC/UL数据 IEC/UL Data	IEC UL	2353XX/010	2-24
额定电流 Rated current [A]	17.5 10		
额定电压 Rated voltage [V]	630 300		
硬导线截面积 Solid [mm²][AWG]	0.2-2.5 24-14		
柔性导线截面积 Flexible [mm²][AWG]	0.2-2.5 24-14		
额定冲击电压 Rated impulse voltage [KV]	6.0 -		
锁线螺钉 Locking crew	-		
扭矩 Torque [N·m]	-		
固定螺钉 Fixed screw	-		
扭矩 Torque [N·m]	-		
剥线长度 Strip length [mm]	9-10		


235系列单孔PCB端子排 235 Series single hole PCB terminal block 间距 Pitch: 10.0mm

产品信息Product Information		订货号/通道数 Order /Poles No.	
IEC/UL数据 IEC/UL Data	IEC UL	2354XX/010	2-24
额定电流 Rated current [A]	17.5 10		
额定电压 Rated voltage [V]	1000 300		
硬导线截面积 Solid [mm²][AWG]	0.2-1.5 24-16		
柔性导线截面积 Flexible [mm²][AWG]	0.2-1.5 24-16		
额定冲击电压 Rated impulse voltage [KV]	8.0 -		
锁线螺钉 Locking crew	-		
扭矩 Torque [N·m]	-		
固定螺钉 Fixed screw	-		
扭矩 Torque [N·m]	-		
剥线长度 Strip length [mm]	9-10		



239系列单孔PCB端子排 239 Series single hole PCB terminal block 间距 Pitch: 3.5mm

产品信息Product Information		订货号/通道数 Order /Poles No.	
IEC/UL数据 IEC/UL Data	IEC UL	2393XX/010	2-24
额定电流 Rated current [A]	17.5 6		
额定电压 Rated voltage [V]	160 300		
硬导线截面积 Solid [mm²][AWG]	0.2-1.5 24-16		
柔性导线截面积 Flexible [mm²][AWG]	0.2-1.5 24-16		
额定冲击电压 Rated impulse voltage [KV]	2.5 -		
锁线螺钉 Locking crew	-		
扭矩 Torque [N·m]	-		
固定螺钉 Fixed screw	-		
扭矩 Torque [N·m]	-		
剥线长度 Strip length [mm]	5-6		



239系列单孔PCB端子排 239 Series single hole PCB terminal block 间距 Pitch: 5.0mm

产品信息Product Information		订货号/通道数 Order /Poles No.	
IEC/UL数据 IEC/UL Data	IEC UL	2391XX	2-24
额定电流 Rated current [A]	24 12		
额定电压 Rated voltage [V]	320 300		
硬导线截面积 Solid [mm²][AWG]	0.2-2.5 24-14		
柔性导线截面积 Flexible [mm²][AWG]	0.2-2.5 24-14		
额定冲击电压 Rated impulse voltage [KV]	4.0 -		
锁线螺钉 Locking crew	-		
扭矩 Torque [N·m]	-		
固定螺钉 Fixed screw	-		
扭矩 Torque [N·m]	-		
剥线长度 Strip length [mm]	8-9		



239系列单孔PCB端子排 239 Series single hole PCB terminal block 间距 Pitch: 7.5mm

产品信息Product Information		订货号/通道数 Order /Poles No.	
IEC/UL数据 IEC/UL Data	IEC UL	2392XX	2-24
额定电流 Rated current [A]	24 12		
额定电压 Rated voltage [V]	630 300		
硬导线截面积 Solid [mm²][AWG]	0.2-2.5 24-14		
柔性导线截面积 Flexible [mm²][AWG]	0.2-2.5 24-14		
额定冲击电压 Rated impulse voltage [KV]	6.0 -		
锁线螺钉 Locking crew	-		
扭矩 Torque [N·m]	-		
固定螺钉 Fixed screw	-		
扭矩 Torque [N·m]	-		
剥线长度 Strip length [mm]	8-9		




239系列单孔PCB端子排 239 Series single hole PCB terminal block 间距 Pitch: 5.08mm

产品信息Product Information		订货号/通道数 Order /Poles No.	
IEC/UL数据 IEC/UL Data	IEC UL	23915X	2-24
额定电流 Rated current [A]	24 12		
额定电压 Rated voltage [V]	320 300		
硬导线截面积 Solid [mm²][AWG]	0.2-2.5 24-14		
柔性导线截面积 Flexible [mm²][AWG]	0.2-2.5 24-14		
额定冲击电压 Rated impulse voltage [KV]	4.0 -		
锁线螺钉 Locking crew	-		
扭矩 Torque [N·m]	-		
固定螺钉 Fixed screw	-		
扭矩 Torque [N·m]	-		
剥线长度 Strip length [mm]	8-9		


239系列单孔PCB端子排 239 Series single hole PCB terminal block 间距 Pitch: 7.62mm

产品信息Product Information		订货号/通道数 Order /Poles No.	
IEC/UL数据 IEC/UL Data	IEC UL	23925X	2-24
额定电流 Rated current [A]	24 12		
额定电压 Rated voltage [V]	630 300		
硬导线截面积 Solid [mm²][AWG]	0.2-2.5 24-14		
柔性导线截面积 Flexible [mm²][AWG]	0.2-2.5 24-14		
额定冲击电压 Rated impulse voltage [KV]	6.0 -		
锁线螺钉 Locking crew	-		
扭矩 Torque [N·m]	-		
固定螺钉 Fixed screw	-		
扭矩 Torque [N·m]	-		
剥线长度 Strip length [mm]	8-9		

245系列PCB端子排 245 Series PCB terminal block 间距 Pitch: 5.0mm

产品信息Product Information		订货号/通道数 Order /Poles No.	
IEC/UL数据 IEC/UL Data	IEC UL	2452XX/020	2-24
额定电流 Rated current [A]	32 20		
额定电压 Rated voltage [V]	320 300		
硬导线截面积 Solid [mm²][AWG]	0.2-4.0 24-12		
柔性导线截面积 Flexible [mm²][AWG]	0.2-4.0 24-12		
额定冲击电压 Rated impulse voltage [KV]	4.0 -		
锁线螺钉 Locking crew	-		
扭矩 Torque [N·m]	-		
固定螺钉 Fixed screw	-		
扭矩 Torque [N·m]	-		
剥线长度 Strip length [mm]	8-9		

245系列PCB端子排 245 Series PCB terminal block 间距 Pitch: 7.5mm

产品信息Product Information		订货号/通道数 Order /Poles No.	
IEC/UL数据 IEC/UL Data	IEC UL	2453XX/020	2-24
额定电流 Rated current [A]	32 20		
额定电压 Rated voltage [V]	630 300		
硬导线截面积 Solid [mm²][AWG]	0.2-4.0 24-12		
柔性导线截面积 Flexible [mm²][AWG]	0.2-4.0 24-12		
额定冲击电压 Rated impulse voltage [KV]	6.0 -		
锁线螺钉 Locking crew	-		
扭矩 Torque [N·m]	-		
固定螺钉 Fixed screw	-		
扭矩 Torque [N·m]	-		
剥线长度 Strip length [mm]	8-9		