

245系列PCB端子排 245 Series PCB terminal block 间距 Pitch: 10.0mm

产品信息Product Information		订货号/通道数 Order / Poles No.	
IEC/UL数据 IEC/UL Data	IEC UL	2454XX/020	2-24
额定电流 Rated current [A]	32 20		
额定电压 Rated voltage [V]	1000 300		
硬导线截面积 Solid [mm²][AWG]	0.2-4.0 24-12		
柔性导线截面积 Flexible [mm²][AWG]	0.2-4.0 24-12		
额定冲击电压 Rated impulse voltage [KV]	8.0 -		
锁线螺钉 Locking crew	-		
扭矩 Torque [N·m]	-		
固定螺钉 Fixed screw	-		
扭矩 Torque [N·m]	-		
剥线长度 Strip length [mm]	8-9		



246系列PCB端子排 246 Series PCB terminal block 间距 Pitch: 7.5mm

产品信息Product Information		订货号/通道数 Order / Poles No.	
IEC/UL数据 IEC/UL Data	IEC UL	2463XX/020	2-24
额定电流 Rated current [A]	41 30		
额定电压 Rated voltage [V]	630 300		
硬导线截面积 Solid [mm²][AWG]	0.2-6.0 24-10		
柔性导线截面积 Flexible [mm²][AWG]	0.2-6.0 24-10		
额定冲击电压 Rated impulse voltage [KV]	6.0 -		
锁线螺钉 Locking crew	-		
扭矩 Torque [N·m]	-		
固定螺钉 Fixed screw	-		
扭矩 Torque [N·m]	-		
剥线长度 Strip length [mm]	8-9		


246系列PCB端子排 246 Series PCB terminal block 间距 Pitch: 10.0mm

产品信息Product Information		订货号/通道数 Order / Poles No.	
IEC/UL数据 IEC/UL Data	IEC UL	2464XX/020	2-24
额定电流 Rated current [A]	41 30		
额定电压 Rated voltage [V]	1000 300		
硬导线截面积 Solid [mm²][AWG]	0.2-6.0 24-10		
柔性导线截面积 Flexible [mm²][AWG]	0.2-6.0 24-10		
额定冲击电压 Rated impulse voltage [KV]	8.0 -		
锁线螺钉 Locking crew	-		
扭矩 Torque [N·m]	-		
固定螺钉 Fixed screw	-		
扭矩 Torque [N·m]	-		
剥线长度 Strip length [mm]	11-12		

250系列PCB端子排 250 Series PCB terminal block 间距 Pitch: 3.5mm

产品信息Product Information		订货号/通道数 Order / Poles No.	
IEC/UL数据 IEC/UL Data	IEC UL	2501XX	2-24
额定电流 Rated current [A]	8 5		
额定电压 Rated voltage [V]	160 300		
硬导线截面积 Solid [mm²][AWG]	0.2-1.5 24-16		
柔性导线截面积 Flexible [mm²][AWG]	0.2-1.5 24-16		
额定冲击电压 Rated impulse voltage [KV]	2.5 -		
锁线螺钉 Locking crew	-		
扭矩 Torque [N·m]	-		
固定螺钉 Fixed screw	-		
扭矩 Torque [N·m]	-		
剥线长度 Strip length [mm]	8.5-9.5		

250系列PCB端子排 250 Series PCB terminal block 间距 Pitch: 5.0mm

产品信息Product Information		订货号/通道数 Order / Poles No.	
IEC/UL数据 IEC/UL Data	IEC UL	2505XX	2-24 (双层)
额定电流 Rated current [A]	10 10		
额定电压 Rated voltage [V]	320 300		
硬导线截面积 Solid [mm²][AWG]	0.5-1.5 20-16		
柔性导线截面积 Flexible [mm²][AWG]	0.5-1.5 20-16		
额定冲击电压 Rated impulse voltage [KV]	4.0 -		
锁线螺钉 Locking crew	-		
扭矩 Torque [N·m]	-		
固定螺钉 Fixed screw	-		
扭矩 Torque [N·m]	-		
剥线长度 Strip length [mm]	9-10		



255系列PCB端子排 255 Series PCB terminal block 间距 Pitch: 5.0mm

产品信息Product Information		订货号/通道数 Order / Poles No.	
IEC/UL数据 IEC/UL Data	IEC UL	2554XX	2-24
额定电流 Rated current [A]	24 15		
额定电压 Rated voltage [V]	320 300		
硬导线截面积 Solid [mm²][AWG]	0.2-2.5 24-14		
柔性导线截面积 Flexible [mm²][AWG]	0.2-2.5 24-14		
额定冲击电压 Rated impulse voltage [KV]	4.0 -		
锁线螺钉 Locking crew	-		
扭矩 Torque [N·m]	-		
固定螺钉 Fixed screw	-		
扭矩 Torque [N·m]	-		
剥线长度 Strip length [mm]	5-6		


255系列PCB端子排 255 Series PCB terminal block 间距 Pitch: 7.5mm

产品信息Product Information		订货号/通道数 Order / Poles No.	
IEC/UL数据 IEC/UL Data	IEC UL	2555XX	2-24
额定电流 Rated current [A]	24 15		
额定电压 Rated voltage [V]	630 300		
硬导线截面积 Solid [mm²][AWG]	0.2-2.5 24-14		
柔性导线截面积 Flexible [mm²][AWG]	0.2-2.5 24-14		
额定冲击电压 Rated impulse voltage [KV]	6.0 -		
锁线螺钉 Locking crew	-		
扭矩 Torque [N·m]	-		
固定螺钉 Fixed screw	-		
扭矩 Torque [N·m]	-		
剥线长度 Strip length [mm]	5-6		

256系列PCB端子排 256 Series PCB terminal block 间距 Pitch: 5.0mm

产品信息Product Information		订货号/通道数 Order / Poles No.	
IEC/UL数据 IEC/UL Data	IEC UL	2563XX	2-24
额定电流 Rated current [A]	24 15		
额定电压 Rated voltage [V]	320 300		
硬导线截面积 Solid [mm²][AWG]	0.2-2.5 24-14		
柔性导线截面积 Flexible [mm²][AWG]	0.2-2.5 24-14		
额定冲击电压 Rated impulse voltage [KV]	4.0 -		
锁线螺钉 Locking crew	-		
扭矩 Torque [N·m]	-		
固定螺钉 Fixed screw	-		
扭矩 Torque [N·m]	-		
剥线长度 Strip length [mm]	5-6		

256系列PCB端子排 256 Series PCB terminal block 间距 Pitch: 7.5mm

产品信息Product Information		订货号/通道数 Order / Poles No.	
IEC/UL数据 IEC/UL Data	IEC UL	2564XX	2-24
额定电流 Rated current [A]	24 15		
额定电压 Rated voltage [V]	320 300		
硬导线截面积 Solid [mm²][AWG]	0.2-2.5 24-14		
柔性导线截面积 Flexible [mm²][AWG]	0.2-2.5 24-14		
额定冲击电压 Rated impulse voltage [KV]	4.0 -		
锁线螺钉 Locking crew	-		
扭矩 Torque [N·m]	-		
固定螺钉 Fixed screw	-		
扭矩 Torque [N·m]	-		
剥线长度 Strip length [mm]	5-6		

256系列PCB端子排 256 Series PCB terminal block 间距 Pitch: 10.0mm

产品信息Product Information		订货号/通道数 Order / Poles No.	
IEC/UL数据 IEC/UL Data	IEC UL	2569XX	2-24
额定电流 Rated current [A]	24 15		
额定电压 Rated voltage [V]	1000 300		
硬导线截面积 Solid [mm²][AWG]	0.2-2.5 24-14		
柔性导线截面积 Flexible [mm²][AWG]	0.2-2.5 24-14		
额定冲击电压 Rated impulse voltage [KV]	8.0 -		
锁线螺钉 Locking crew	-		
扭矩 Torque [N·m]	-		
固定螺钉 Fixed screw	-		
扭矩 Torque [N·m]	-		
剥线长度 Strip length [mm]	11-12		