







257系列PCB端子排 257 Series PCB terminal block 间距 Pitch: 5.0mm

产品信息Product Information		订货号/通道数 Order /Poles No.	
IEC/UL数据 IEC/UL Data	IEC UL	2572XX	2-24 (双层)
额定电流 Rated current	[A] 21 10	   	
额定电压 Rated voltage	[V] 320 300		
硬导线截面积 Solid	[mm²][AWG] 0.2-2.5 24-14		
柔性导线截面积 Flexible	[mm²][AWG] 0.2-2.5 24-14		
额定冲击电压 Rated impulse voltage	[KV] 4.0 -		
锁线螺钉 Locking crew	-		
扭矩 Torque	[N·m] -		
固定螺钉 Fixed screw	-	   	
扭矩 Torque	[N·m] -		
剥线长度 Strip length	[mm] 5-6		



257系列PCB端子排 257 Series PCB terminal block 间距 Pitch: 7.5mm

产品信息Product Information		订货号/通道数 Order /Poles No.	
IEC/UL数据 IEC/UL Data	IEC UL	2573XX	2-24 (双层)
额定电流 Rated current	[A] 21 10	   	
额定电压 Rated voltage	[V] 630 300		
硬导线截面积 Solid	[mm²][AWG] 0.2-2.5 24-14		
柔性导线截面积 Flexible	[mm²][AWG] 0.2-2.5 24-14		
额定冲击电压 Rated impulse voltage	[KV] 6.0 -		
锁线螺钉 Locking crew	-		
扭矩 Torque	[N·m] -		
固定螺钉 Fixed screw	-	   	
扭矩 Torque	[N·m] -		
剥线长度 Strip length	[mm] 5-6		


246系列PCB端子排 246 Series PCB terminal block 间距 Pitch: 10.0mm

产品信息Product Information		订货号/通道数 Order /Poles No.	
IEC/UL数据 IEC/UL Data	IEC UL	2574XX	2-24 (双层)
额定电流 Rated current	[A] 21 10	   	
额定电压 Rated voltage	[V] 1000 300		
硬导线截面积 Solid	[mm²][AWG] 0.2-2.5 24-14		
柔性导线截面积 Flexible	[mm²][AWG] 0.2-2.5 24-14		
额定冲击电压 Rated impulse voltage	[KV] 8.0 -		
锁线螺钉 Locking crew	-		
扭矩 Torque	[N·m] -		
固定螺钉 Fixed screw	-	   	
扭矩 Torque	[N·m] -		
剥线长度 Strip length	[mm] 5-6		

258系列PCB端子排 258 Series PCB terminal block 间距 Pitch: 5.0mm

产品信息Product Information		订货号/通道数 Order /Poles No.	
IEC/UL数据 IEC/UL Data	IEC UL	2582XX	2-24 (三层)
额定电流 Rated current	[A] 21 20	   	
额定电压 Rated voltage	[V] 320 300		
硬导线截面积 Solid	[mm²][AWG] 0.2-2.5 24-12		
柔性导线截面积 Flexible	[mm²][AWG] 0.2-2.5 24-12		
额定冲击电压 Rated impulse voltage	[KV] 4.0 -		
锁线螺钉 Locking crew	-		
扭矩 Torque	[N·m] -		
固定螺钉 Fixed screw	-	   	
扭矩 Torque	[N·m] -		
剥线长度 Strip length	[mm] 5-6		

258系列PCB端子排 258 Series PCB terminal block 间距 Pitch: 7.5mm

产品信息Product Information		订货号/通道数 Order /Poles No.	
IEC/UL数据 IEC/UL Data	IEC UL	2583XX	2-24 (三层)
额定电流 Rated current	[A] 21 10	   	
额定电压 Rated voltage	[V] 630 300		
硬导线截面积 Solid	[mm²][AWG] 0.2-2.5 24-14		
柔性导线截面积 Flexible	[mm²][AWG] 0.2-2.5 24-14		
额定冲击电压 Rated impulse voltage	[KV] 6.0 -		
锁线螺钉 Locking crew	-		
扭矩 Torque	[N·m] -		
固定螺钉 Fixed screw	-	   	
扭矩 Torque	[N·m] -		
剥线长度 Strip length	[mm] 5-6		

