

5.0mm间距孔型插头带焊针 5.0mm Female connector with spring-cage clamp with solder pin

产品信息Product Information				产品信息Product Information				订货号/通道数 Order / Poles No.		附件Accessory	
IEC/UL数据 IEC/UL Data				IEC				UL			
额定电流 Rated current	[A]	12	15	锁线螺钉 Locking crew	[N·m]	-		45025X	2-24		
额定电压 Rated voltage	[V]	320	300	扭矩 Torque	[N·m]	-		45025X/110	2-24		
硬导线截面积 Solid	[mm²][AWG]	-	-	固定螺钉 Fixed screw	[N·m]	-		45035X	2-24		
柔性导线截面积 Flexible	[mm²][AWG]	-	-	扭矩 Torque	[N·m]	-					
额定冲击电压 Rated impulse voltage	[KV]	4.0	-	剥线长度 Strip length	[mm]						

45025X	45025X/110	45035X
直针型vertical solder pin	长直针型long solder pin	弯针型right angle solder pin

5.0mm间距孔型连接器(防错) 5.0mm Female connectors(protected against mismatching)

产品信息Product Information				产品信息Product Information				订货号/通道数 Order / Poles No.		附件Accessory	
IEC/UL数据 IEC/UL Data				IEC				UL			
额定电流 Rated current	[A]	12	15	锁线螺钉 Locking crew	[N·m]	-		4506XX	2-24	45097X	450012
额定电压 Rated voltage	[V]	320	300	扭矩 Torque	[N·m]	-		4506XX/010	2-24	4505XX	22533X
硬导线截面积 Solid	[mm²][AWG]	0.2-2.5	28-12	固定螺钉 Fixed screw	[N·m]	-		4506XX/030	2-24	450021	
柔性导线截面积 Flexible	[mm²][AWG]	0.2-2.5	28-12	扭矩 Torque	[N·m]	-		4506XX/050	2-24	450023	
额定冲击电压 Rated impulse voltage	[KV]	4.0	-	剥线长度 Strip length	[mm]	8-9				450014	

4506XX	4506XX/010	4506XX/030
带固定脚with fixing flange	带固定脚with fixing flange	带脚钉with snap in mounting feet
4506XX/050		
带卡接脚with locking device		

5.0mm间距穿墙式连接器 5.0mm Through-wall connector

产品信息Product Information				产品信息Product Information				订货号/通道数 Order / Poles No.		附件Accessory	
IEC/UL数据 IEC/UL Data				IEC				UL			
额定电流 Rated current	[A]	12	15	锁线螺钉 Locking crew	[N·m]	-		45046X	2-24	45097X	450012
额定电压 Rated voltage	[V]	320	300	扭矩 Torque	[N·m]	-		45046X/010	2-24	4505XX	22533X
硬导线截面积 Solid	[mm²][AWG]	0.2-2.5	28-12	固定螺钉 Fixed screw	[N·m]	-		45043X	2-24	450021	
柔性导线截面积 Flexible	[mm²][AWG]	0.2-2.5	28-12	扭矩 Torque	[N·m]	-		45043X/010	2-24	450023	
额定冲击电压 Rated impulse voltage	[KV]	4.0	-	剥线长度 Strip length	[mm]	8-9				450014	

45046X	45046X/010
直针型vertical solder pin	直针型带固定脚 vertical solder pin with fixing flange
45043X	45043X/010
弯针型with fixing flange	弯针型带固定脚 right angle solder pin with fixing flange

5.0mm间距针型连接器(防错) 5.0mm Male connector with spring-cage clamp (protected against mismatching)

产品信息Product Information				产品信息Product Information				订货号/通道数 Order / Poles No.		附件Accessory	
IEC/UL数据 IEC/UL Data				IEC				UL			
额定电流 Rated current	[A]	12	15	锁线螺钉 Locking crew	[N·m]	-		4509XX	2-24	45097X	450012
额定电压 Rated voltage	[V]	320	300	扭矩 Torque	[N·m]	-		4509XX/010	2-24	4505XX	22533X
硬导线截面积 Solid	[mm²][AWG]	0.2-2.5	28-12	固定螺钉 Fixed screw	[N·m]	-		4509XX/030	2-24	450021	
柔性导线截面积 Flexible	[mm²][AWG]	0.2-2.5	28-12	扭矩 Torque	[N·m]	-		4509XX/010	2-24	450023	
额定冲击电压 Rated impulse voltage	[KV]	4.0	-	剥线长度 Strip length	[mm]	8-9				450014	

4509XX	4509XX/010	4509XX/030
带固定脚with fixing flange	带固定脚with fixing flange	带脚钉with snap in mounting feet
4509XX/060		
带穿墙固定脚with mounting ears		