



	2.5mm ² 一进两出接线端子 1-2 Feed Through Terminal Block			4mm ² 一进两出接线端子 1-2 Feed Through Terminal Block		
	技术参数Technical Parameter			技术参数Technical Parameter		
尺寸Size	厚度Thickness	宽度Width	高度Height	厚度Thickness	宽度Width	高度Height
注：安装NS35/7.5导轨后的高度 Note：Height With DIN Rail NS 35/7.5	5.2	60.2	35.2	6.2	66.3	35.5
额定参数Rated Parameters	IEC	UL		IEC	UL	
额定电压Rated Voltage	800	600		800	600	
额定电流Rated Current	24	20		32	30	
接线容量Wire Range	刚性Solid	柔性Fine Stranded	带冷压头Furrule	刚性Solid	柔性Fine Stranded	带冷压头Furrule
	0.2-4	0.2-2.5	0.2-2.5	0.2-6	0.2-4	0.2-4
	26-12	26-12	26-12	24-10	24-10	24-10
其余参数Other Parameters	V0			V0		
绝缘材料/阻燃等级，符合UL94 Insulating Material / Flame Retardant Grade, Conforming To UL94	8-10			8-10		
剥线长度Strip length	[mm]					
产品Product	颜色Colour		订货号Order NO.	颜色Colour		订货号Order NO.
适配NS 35/7.5导轨 Can Be Used For DIN Rail NS 35/7.5	灰Gray		TP2.5-3-GY	灰Gray		TP4-3-GY
	橙Orange		TP2.5-3-OG	橙Orange		TP4-3-OG
	蓝Blue		TP2.5-3-BU	蓝Blue		TP4-3-BU
配套附件Accessory	订货号Order NO.		配套附件Accessory	订货号Order NO.		配套附件Accessory
端板Cover Plate	TC1.5-3-GY-EA		TP4-3-GY-EA	TC1.5-3-OG-EA		TP4-3-OG-EA
厚度2.2mm Thickness2.2mm	TC1.5-3-BU-EA		TP4-3-BU-EA			
补偿端板Compensatory Plate	订货号Order NO.		订货号Order NO.			
厚度1.00mm Thickness1.00mm	*		*			
跨接件Jumper	订货号Order NO.		跨接件Jumper	订货号Order NO.		跨接件Jumper
位数Poles No.	TJA5.2-2		TJA6.2-2	TJA5.2-3		TJA6.2-3
2	TJA5.2-4		TJA6.2-4			
3	TJA5.2-9		TJA6.2-9	TJA5.2-10		TJA6.2-10
4				订货号Order NO.		订货号Order NO.
...	305801		306801	订货号Order NO.		订货号Order NO.
9	TMB5.2-120		TMB6.2-100			
10						
正面标记Front Marker	订货号Order NO.		正面标记和侧面标记Front And Side Marker	订货号Order NO.		正面标记和侧面标记Front And Side Marker
10位PCS			可提供印字服务Printing Service			

6mm ² 一进两出接线端子 1-2 Feed Through Terminal Block			10mm ² 一进两出接线端子 1-2 Feed Through Terminal Block			16mm ² 一进两出接线端子 1-2 Feed Through Terminal Block		
技术参数Technical Parameter			技术参数Technical Parameter			技术参数Technical Parameter		
厚度Thickness	宽度Width	高度Height	厚度Thickness	宽度Width	高度Height	厚度Thickness	宽度Width	高度Height
8.2	74.5	42.2	10.2	88.9	49.6	12.2	100.4	52.6
IEC	UL		IEC	UL		IEC	UL	
1000	600		1000	600		*	*	
41	40		57	60		*	*	
刚性Solid	柔性Fine Stranded	带冷压头Furrule	刚性Solid	柔性Fine Stranded	带冷压头Furrule	刚性Solid	柔性Fine Stranded	带冷压头Furrule
0.5-10	0.5-6	0.5-6	0.5-16	0.5-10	0.5-10	0.5-25	0.5-16	0.5-16
20-8	20-8	20-8	20-6	20-6	20-6	20-4	20-4	20-4
V0			V0			V0		
10-12			18			18		
订货信息Order Information			订货信息Order Information			订货信息Order Information		
订货号Order NO.			订货号Order NO.			订货号Order NO.		
TP6-3-GY			TP10-3-GY			TP16-3-GY		
TP6-3-OG			TP10-3-OG			TP16-3-OG		
TP6-3-BU			TP10-3-BU			TP16-3-BU		
配套附件Accessory			配套附件Accessory			配套附件Accessory		
订货号Order NO.			订货号Order NO.			订货号Order NO.		
TP6-3-GY-EA			TP10-3-GY-EA			TP16-3-GY-EA		
TP6-3-OG-EA			TP10-3-OG-EA			TP10-3-OG-EA		
TP6-3-BU-EA			TP10-3-BU-EA			TP10-3-BU-EA		
订货号Order NO.			订货号Order NO.			订货号Order NO.		
*			*			*		
订货号Order NO.			订货号Order NO.			订货号Order NO.		
TJA8.2-2			TJA10.2-2			TJA12.2-2		
TJA8.2-3			*			*		
TJA8.2-4			*			*		
.....								
TJA8.2-9			*			*		
TJA8.2-10			*			*		
			订货号Order NO.			订货号Order NO.		
308801			TMB10.2-10			TMB10.2-10		
			订货号Order NO.			订货号Order NO.		
TMB8.2-50			TMB8.2-50			TMB8.2-50		