



2.5mm² 直插式带输入7位配电块 Push-in Type Power Distribution Block 2.5mm² 7 Terminal Points				2.5mm² 直插式带输入13位配电块 Push-in Type Power Distribution Block 2.5mm² 13 Terminal Points			
技术参数Technical Parameter				技术参数Technical Parameter			
尺寸Size				尺寸Size			
[mm]				[mm]			
25.6				41.1			
28.6				28.6			
21.7				21.7			
额定参数Rated Parameters				额定参数Rated Parameters			
输入端Input				输入端Input			
IEC				IEC			
500				500			
41				41			
输出端Output				输出端Output			
500				500			
24				24			
接线容量Wire Range				接线容量Wire Range			
输入端Input				输入端Input			
刚性Solid				刚性Solid			
柔性Fine Stranded				柔性Fine Stranded			
带冷压头Furrule				带冷压头Furrule			
0.5-10				0.5-10			
0.5-6				0.5-6			
0.5-6				0.5-6			
20-10				20-10			
20-10				20-10			
20-10				20-10			
输出端Output				输出端Output			
[mm²]				[mm²]			
0.2-4				0.2-4			
0.2-2.5				0.2-2.5			
0.2-2.5				0.2-2.5			
[AWG]				[AWG]			
24-14				24-14			
24-14				24-14			
24-14				24-14			
其余参数Other Parameters				其余参数Other Parameters			
绝缘材料/阻燃等级, 符合UL94 Insulating Material / Flame Retardant Grade, Conforming To UL94				绝缘材料/阻燃等级, 符合UL94 Insulating Material / Flame Retardant Grade, Conforming To UL94			
V0				V0			
输入端Input				输入端Input			
剥线长度Strip Length				剥线长度Strip Length			
[mm]				[mm]			
10-12				10-12			
输出端Output				输出端Output			
剥线长度Strip Length				剥线长度Strip Length			
[mm]				[mm]			
8-10				8-10			
订货信息Order Information				订货信息Order Information			
产品Product				产品Product			
颜色Colour				颜色Colour			
灰Gray				灰Gray			
橙Orange				橙Orange			
蓝Blue				蓝Blue			
配套附件Accessory				配套附件Accessory			
大导轨转换器 Din rail adapter for NS35				大导轨转换器 Din rail adapter for NS35			
小导轨转换器 Din rail adapter for NS15				小导轨转换器 Din rail adapter for NS15			
导轨卡板 Din rail bracket				导轨卡板 Din rail bracket			
螺钉法兰 Flange for screw mounting				螺钉法兰 Flange for screw mounting			
法兰标记支架 Marking carrier				法兰标记支架 Marking carrier			

2.5mm² 直插式带输入19位配电块 Push-in Type Power Distribution Block 2.5mm² 19 Terminal Points			
技术参数Technical Parameter			
尺寸Size			
[mm]			
56.5			
28.6			
21.7			
额定参数Rated Parameters			
输入端Input			
IEC			
500			
41			
输出端Output			
500			
24			
接线容量Wire Range			
输入端Input			
刚性Solid			
柔性Fine Stranded			
带冷压头Furrule			
0.5-10			
0.5-6			
0.5-6			
20-10			
20-10			
20-10			
输出端Output			
[mm²]			
0.2-4			
0.2-2.5			
0.2-2.5			
[AWG]			
24-14			
24-14			
24-14			
其余参数Other Parameters			
绝缘材料/阻燃等级, 符合UL94 Insulating Material / Flame Retardant Grade, Conforming To UL94			
V0			
输入端Input			
剥线长度Strip Length			
[mm]			
10-12			
输出端Output			
剥线长度Strip Length			
[mm]			
8-10			
订货信息Order Information			
产品Product			
颜色Colour			
灰Gray			
橙Orange			
蓝Blue			
配套附件Accessory			
大导轨转换器 Din rail adapter for NS35			
小导轨转换器 Din rail adapter for NS15			
导轨卡板 Din rail bracket			
螺钉法兰 Flange for screw mounting			
法兰标记支架 Marking carrier			

