



	16mm² 一进一出接线端子 1-1 Feed Through Terminal Block			35mm² 一进一出接线端子 1-1 Feed Through Terminal Block		
	技术参数Technical Parameter			技术参数Technical Parameter		
尺寸Size	厚度Thickness	宽度Width	高度Height	厚度Thickness	宽度Width	高度Height
注：安装NS35/7.5导轨后的高度 Note：Height With DIN Rail NS 35/7.5	12.2	80	51.5	16.1	100	59
额定参数Rated Parameters	IEC	UL		IEC	UL	
额定电压Rated Voltage	1000	600		1000	600	
额定电流Rated Current	76	85		125	115	
接线容量Wire Range	刚性Solid	柔性Fine Stranded	带冷压头Furrule	刚性Solid	柔性Fine Stranded	带冷压头Furrule
	0.2-25	0.2-16	0.25-16	2.5-35	2.5-35	2.5-35
	24-4	24-4	24-4	14-2	14-2	14-2
其余参数Other Parameters						
绝缘材料/阻燃等级，符合UL94 Insulating Material / Flame Retardant Grade, Conforming To UL94	V0			V0		
剥线长度Strip length	18			25		
	订货信息Order Information			订货信息Order Information		
产品Product	颜色Colour			订货号Order NO.		
适配NS 35/7.5 NS 35/15导轨 Can Be Used For DIN Rail NS 35/7.5 NS35/15	灰Gray			TC16-2-GY		
	橙Orange			TC16-2-OG		
	蓝Blue			TC16-2-BU		
	配套附件Accessory			配套附件Accessory		
端板Cover Plate	订货号Order NO.			订货号Order NO.		
厚度2.2mm Thickness2.2mm	灰Gray			*		
	橙Orange			*		
	蓝Blue			*		
补偿端板Compensatory Plate	订货号Order NO.			订货号Order NO.		
厚度1.00mm Thickness1.00mm	*			*		
跨接件Jumper						
位数Poles No.	颜色Colour			订货号Order NO.		
2	黄Yellow			*		
3	黄Yellow			*		
4	黄Yellow			*		
...						
9	黄Yellow			*		
10	黄Yellow			*		
安全警告标记 Protective Warning Marker	订货号Order NO.			订货号Order NO.		
5位PCS	TMD10.2-5			TMD10.2-5		
正面标记Front Marker	订货号Order NO.			订货号Order NO.		
10位PCS	TMB10.2-10			TMB10.2-10		
正面标记和侧面标记Front And Side Marker	订货号Order NO.			订货号Order NO.		
可提供印字服务Printing Service	TMB8.2-50			TMB8.2-50		



	1.5mm² 一进一出接地端子 1-1 Feed Through Ground Terminal Block			2.5mm² 一进一出接地端子 1-1 Feed Through Ground Terminal Block		
	技术参数Technical Parameter			技术参数Technical Parameter		
尺寸Size	厚度Thickness	宽度Width	高度Height	厚度Thickness	宽度Width	高度Height
注：安装NS35/7.5导轨后的高度 Note：Height With DIN Rail NS 35/7.5	4.2	48.2	36.8	5.2	48.2	36.8
额定参数Rated Parameters	IEC	UL		IEC	UL	
额定电压Rated Voltage	500	300		800	600	
额定电流Rated Current	*	*		*	*	
接线容量Wire Range	刚性Solid	柔性Fine Stranded	带冷压头Furrule	刚性Solid	柔性Fine Stranded	带冷压头Furrule
	0.2-1.5	0.2-1.5	0.2-1.5	0.2-4	0.2-2.5	0.2-2.5
	24-16	24-16	24-16	24-12	24-12	24-12
其余参数Other Parameters						
绝缘材料/阻燃等级，符合UL94 Insulating Material / Flame Retardant Grade, Conforming To UL94	V0			V0		
剥线长度Strip length	10			10		
	订货信息Order Information			订货信息Order Information		
产品Product	颜色Colour			订货号Order NO.		
适配NS 35/7.5 NS 35/15导轨 Can Be Used For DIN Rail NS 35/7.5 NS35/15	黄绿Yellow green			TC1.5-2-PE		
	*			*		
	*			*		
	配套附件Accessory			配套附件Accessory		
端板Cover Plate	订货号Order NO.			订货号Order NO.		
厚度2.2mm Thickness2.2mm	灰Gray			TC1.5-2-GY-EA		
	橙Orange			TC1.5-2-OG-EA		
	蓝Blue			TC1.5-2-BU-EA		
补偿端板Compensatory Plate	订货号Order NO.			订货号Order NO.		
厚度1.00mm Thickness1.00mm	灰Gray			TC1.5-4-GY-EB		
跨接件Jumper						
位数Poles No.	颜色Colour			订货号Order NO.		
2	黄Yellow			*		
3	黄Yellow			*		
4	黄Yellow			*		
...						
9	黄Yellow			*		
10	黄Yellow			*		
安全警告标记 Protective Warning Marker	订货号Order NO.			订货号Order NO.		
5位PCS	TMD4.2-5			TMD5.2-5		
正面标记Front Marker	订货号Order NO.			订货号Order NO.		
10位PCS	*			305801		
正面标记和侧面标记Front And Side Marker	订货号Order NO.			订货号Order NO.		
可提供印字服务Printing Service	TMB4.2-100			TMB5.2-120		