





		4mm ² 一进一出接地端子 1-1 Feed Through Ground Terminal Block			6mm ² 一进一出接地端子 1-1 Feed Through Ground Terminal Block		
		技术参数Technical Parameter			技术参数Technical Parameter		
尺寸Size		厚度Thickness	宽度Width	高度Height	厚度Thickness	宽度Width	高度Height
注：安装NS35/7.5导轨后的高度 Note：Height With DIN Rail NS 35/7.5		6.2	56.2	36.8	8.2	69.5	43.5
额定参数Rated Parameters		IEC	UL		IEC	UL	
额定电压Rated Voltage		800	600		1000	600	
额定电流Rated Current		*	*		*	*	
接线容量Wire Range		刚性Solid	柔性Fine Stranded	带冷压头Furrule	刚性Solid	柔性Fine Stranded	带冷压头Furrule
		0.2-6	0.2-4	0.2-4	0.2-10	0.2-6	0.2-6
		24-10	24-10	24-10	24-8	24-8	24-8
其余参数Other Parameters							
绝缘材料/阻燃等级，符合UL94 Insulating Material / Flame Retardant Grade, Conforming To UL94		V0			V0		
剥线长度Strip length		10			12		
		订货信息Order Information			订货信息Order Information		
产品Product		订货号Order NO.			订货号Order NO.		
颜色Colour		TC4-2-PE			TC6-2-PE		
适配NS 35/7.5 NS 35/15导轨 Can Be Used For DIN Rail		*			*		
NS 35/7.5 NS35/15		*			*		
		配套附件Accessory			配套附件Accessory		
端板Cover Plate		订货号Order NO.			订货号Order NO.		
		TC4-2-GY-EA			TC6-2-GY-EA		
厚度2.2mm Thickness2.2mm		TC4-2-OG-EA			TC6-2-OG-EA		
		TC4-2-BU-EA			TC6-2-BU-EA		
补偿端板Compensatory Plate		订货号Order NO.			订货号Order NO.		
厚度1.00mm Thickness1.00mm		TC4-4-GY-EB			*		
跨接件Jumper							
位数Poles No.		订货号Order NO.			订货号Order NO.		
2		*			TJA8.2-2		
3		*			TJA8.2-3		
4		*			TJA8.2-4		
...							
9		*			TJA8.2-9		
10		*			TJA8.2-10		
安全警告标记 Protective Warning Marker		订货号Order NO.			订货号Order NO.		
5位PCS		TMD6.2-5			TMD8.2-5		
正面标记Front Marker		订货号Order NO.			订货号Order NO.		
10位PCS		306801			308801		
正面标记和侧面标记Front And Side Marker		订货号Order NO.			订货号Order NO.		
可提供印字服务Printing Service		TMB6.2-100			TMB8.2-50		



10mm ² 一进一出接地端子 1-1 Feed Through Ground Terminal Block		
技术参数Technical Parameter		
厚度Thickness	宽度Width	高度Height
10.2	71.5	49.6
IEC	UL	
800	600	
*	*	
刚性Solid	柔性Fine Stranded	带冷压头Furrule
0.2-16	0.2-10	0.2-10
24-6	24-6	24-6
其余参数Other Parameters		
绝缘材料/阻燃等级，符合UL94 Insulating Material / Flame Retardant Grade, Conforming To UL94		
剥线长度Strip length		
[mm]		
V0		
18		
订货信息Order Information		
订货号Order NO.		
TC10-2-PE		
*		
*		
配套附件Accessory		
订货号Order NO.		
TC10-2-GY-EA		
厚度2.2mm Thickness2.2mm		
灰Gray		
橙Orange		
蓝Blue		
补偿端板Compensatory Plate		
厚度1.00mm Thickness1.00mm		
灰Gray		
跨接件Jumper		
位数Poles No.		
颜色Colour		
2		
3		
4		
...		
9		
10		
安全警告标记 Protective Warning Marker		
5位PCS		
正面标记Front Marker		
10位PCS		
正面标记和侧面标记Front And Side Marker		
可提供印字服务Printing Service		



16mm ² 一进一出接地端子 1-1 Feed Through Ground Terminal Block		
技术参数Technical Parameter		
厚度Thickness	宽度Width	高度Height
12.2	80	51.5
IEC	UL	
1000	600	
*	*	
刚性Solid	柔性Fine Stranded	带冷压头Furrule
0.2-25	0.2-16	0.25-16
24-4	24-4	24-4
其余参数Other Parameters		
绝缘材料/阻燃等级，符合UL94 Insulating Material / Flame Retardant Grade, Conforming To UL94		
剥线长度Strip length		
[mm]		
V0		
18		
订货信息Order Information		
订货号Order NO.		
TC16-2-PE		
*		
*		
配套附件Accessory		
订货号Order NO.		
TC16-2-GY-EA		
厚度2.2mm Thickness2.2mm		
灰Gray		
橙Orange		
蓝Blue		
补偿端板Compensatory Plate		
厚度1.00mm Thickness1.00mm		
灰Gray		
跨接件Jumper		
位数Poles No.		
颜色Colour		
2		
3		
4		
...		
9		
10		
安全警告标记 Protective Warning Marker		
5位PCS		
正面标记Front Marker		
10位PCS		
正面标记和侧面标记Front And Side Marker		
可提供印字服务Printing Service		



35mm ² 一进一出接地端子 1-1 Feed Through Ground Terminal Block		
技术参数Technical Parameter		
厚度Thickness	宽度Width	高度Height
16.1	100	59
IEC	UL	
1000	600	
*	*	
刚性Solid	柔性Fine Stranded	带冷压头Furrule
2.5-35	2.5-35	2.5-35
14-2	14-2	14-2
其余参数Other Parameters		
绝缘材料/阻燃等级，符合UL94 Insulating Material / Flame Retardant Grade, Conforming To UL94		
剥线长度Strip length		
[mm]		
V0		
25		
订货信息Order Information		
订货号Order NO.		
TC35-2-PE		
*		
*		
配套附件Accessory		
订货号Order NO.		
TC35-2-GY-EA		
厚度2.2mm Thickness2.2mm		
灰Gray		
橙Orange		
蓝Blue		
补偿端板Compensatory Plate		
厚度1.00mm Thickness1.00mm		
灰Gray		
跨接件Jumper		
位数Poles No.		
颜色Colour		
2		
3		
4		
...		
9		
10		
安全警告标记 Protective Warning Marker		
5位PCS		
正面标记Front Marker		
10位PCS		
正面标记和侧面标记Front And Side Marker		
可提供印字服务Printing Service		