



2.5mm² 一进一出插拔接线端子
1-1 Feed Through Plug-in Terminal Block

2.5mm² 双层插拔接线端子
Double-level Pluggable Terminal Block

技术参数Technical Parameter	
厚度Thickness	宽度Width
5.2	68
IEC	UL
500	300
24	20
刚性Solid	柔性Fine Stranded
0.2-4	0.2-2.5
24-12	24-12
其余参数Other Parameters	
绝缘材料/阻燃等级，符合UL94 Insulating Material / Flame Retardant Grade, Conforming To UL94	
剥线长度Strip length	[mm]
10	
订货信息Order Information	
产品Product	颜色Colour
适配NS 35/7.5 NS 35/15导轨 Can Be Used For DIN Rail NS 35/7.5 NS35/15	灰Gray
	橙Orange
	蓝Blue
配套附件Accessory	
端板Cover Plate	
厚度2.2mm Thickness2.2mm	灰Gray
	橙Orange
	蓝Blue
补偿端板Compensatory Plate	
厚度1.00mm Thickness1.00mm	灰Gray
跨接件Jumper	
位数Poles No.	颜色Colour
2	黄Yellow
3	黄Yellow
4	黄Yellow
...	
9	黄Yellow
10	黄Yellow
安全警告标记 Protective Warning Marker	
5位PCS	
正面标记Front Marker	
10位PCS	
正面标记和侧面标记Front And Side Marker	
可提供印字服务Printing Service	

技术参数Technical Parameter		
厚度Thickness	宽度Width	高度Height
5.2	68	47.5
IEC	UL	
500	300	
24	20	
刚性Solid	柔性Fine Stranded	带冷压头Furrule
0.2-4	0.2-2.5	0.2-2.5
24-12	24-12	24-12
V0		
10		
订货信息Order Information		
订货号Order NO.		
TC2.5-2-1-GY		
TC2.5-2-1-OG		
TC2.5-2-1-BU		
配套附件Accessory		
订货号Order NO.		
TC1.5-2-GY-EA		
TC1.5-2-OG-EA		
TC1.5-2-BU-EA		
订货号Order NO.		
*		
Imax/24A		
订货号Order NO.		
TJA5.2-2		
TJA5.2-3		
TJA5.2-4		
.....		
TJA5.2-9		
TJA5.2-10		
订货号Order NO.		
TMD5.2-5		
订货号Order NO.		
305801		
订货号Order NO.		
TMB5.2-120		

技术参数Technical Parameter		
厚度Thickness	宽度Width	高度Height
5.2	71.5	46
IEC	UL	
500	600	
22	20	
刚性Solid	柔性Fine Stranded	带冷压头Furrule
0.2-4	0.2-2.5	0.2-2.5
24-12	24-12	24-12
V0		
10		
订货信息Order Information		
订货号Order NO.		
TCD2.5-2-1-GY		
TCD2.5-2-1-OG		
TCD2.5-2-1-BU		
配套附件Accessory		
订货号Order NO.		
TCD2.5-2-1-GY-EA		
TCD2.5-2-1-OG-EA		
TCD2.5-2-1-BU-EA		
订货号Order NO.		
*		
Imax/24A		
订货号Order NO.		
TJA5.2-2		
TJA5.2-3		
TJA5.2-4		
.....		
TJA5.2-9		
TJA5.2-10		
订货号Order NO.		
TMD5.2-5		
订货号Order NO.		
*		
订货号Order NO.		
TMB5.2-120		



2.5mm² 双层等电位插拔接线端子
Double Level With Equipotential Bonder Plug-in Terminal Block

技术参数Technical Parameter		
厚度Thickness	宽度Width	高度Height
5.2	71.5	46
IEC	UL	
500	600	
22	20	
刚性Solid	柔性Fine Stranded	带冷压头Furrule
0.2-4	0.2-2.5	0.2-2.5
24-12	24-12	24-12
V0		
10		
订货信息Order Information		
订货号Order NO.		
TCD2.5-2-1-PV(黑色)		
*		
*		
配套附件Accessory		
订货号Order NO.		
TCD2.5-2-1-GY-EA		
TCD2.5-2-1-OG-EA		
TCD2.5-2-1-BU-EA		
订货号Order NO.		
*		
Imax/24A		
订货号Order NO.		
TJA5.2-2		
TJA5.2-3		
TJA5.2-4		
.....		
TJA5.2-9		
TJA5.2-10		
订货号Order NO.		
TMD5.2-5		
订货号Order NO.		
*		
订货号Order NO.		
TMB5.2-120		



2.5mm² 一进一出插拔接地端子
1-1 Feed Through Ground Plug-in Terminal Block

技术参数Technical Parameter	
厚度Thickness	宽度Width
5.2	68
IEC	UL
500	300
*	*
刚性Solid	柔性Fine Stranded
0.2-4	0.2-2.5
24-12	24-12
其余参数Other Parameters	
绝缘材料/阻燃等级，符合UL94 Insulating Material / Flame Retardant Grade, Conforming To UL94	
剥线长度Strip length	[mm]
10	
订货信息Order Information	
产品Product	颜色Colour
适配NS 35/7.5 NS 35/15导轨 Can Be Used For DIN Rail NS 35/7.5 NS35/15	黄绿Yellow green
	*
	*
配套附件Accessory	
端板Cover Plate	
厚度2.2mm Thickness2.2mm	灰Gray
	橙Orange
	蓝Blue
补偿端板Compensatory Plate	
厚度1.00mm Thickness1.00mm	灰Gray
跨接件Jumper	
位数Poles No.	颜色Colour
2	黄Yellow
3	黄Yellow
4	黄Yellow
...	
9	黄Yellow
10	黄Yellow
安全警告标记 Protective Warning Marker	
5位PCS	
正面标记Front Marker	
10位PCS	
正面标记和侧面标记Front And Side Marker	
可提供印字服务Printing Service	

技术参数Technical Parameter		
厚度Thickness	宽度Width	高度Height
5.2	68	47.5
IEC	UL	
500	300	
*	*	
刚性Solid	柔性Fine Stranded	带冷压头Furrule
0.2-4	0.2-2.5	0.2-2.5
24-12	24-12	24-12
V0		
10		
订货信息Order Information		
订货号Order NO.		
TC2.5-2-1-PE		
*		
*		
配套附件Accessory		
订货号Order NO.		
TC1.5-2-GY-EA		
TC1.5-2-OG-EA		
TC1.5-2-BU-EA		
订货号Order NO.		
*		
订货号Order NO.		
*		
*		
*		
.....		
*		
*		
订货号Order NO.		
TMD5.2-5		
订货号Order NO.		
305801		
订货号Order NO.		
TMB5.2-120		