



2.5mm² TU接线端子

TU Terminal Block

技术参数Technical Parameter			
尺寸Size	厚度Thickness	宽度Width	高度Height
注：安装NS35/7.5导轨后的高度 Note：Height With DIN Rail NS 35/7.5	[mm]	5.2	47.3
额定参数Rated Parameters	IEC	UL	
额定电压Rated Voltage	[V]	1000	600
额定电流Rated Current	[A]	24	20
接线容量Wire Range	刚性Solid	柔性Fine Stranded	带冷压头Furrule
	[mm ²]	0.2-4	0.2-2.5
	[AWG]	26-12	26-12
螺钉类型Screw Type	M2.5		
扭矩Torque	[N.m]	0.4	
其余参数Other Parameters			
绝缘材料/阻燃等级，符合UL94 Insulating Material / Flame Retardant Grade, Conforming To UL94	V0		
剥线长度Strip length	[mm]	8-9	

订货信息Order Information		
产品Product	颜色Colour	订货号Order NO.
适配NS 35/7.5导轨 Can Be Used For DIN Rail NS 35/7.5	灰Gray	TU2.5-2-GY
	橙Orange	TU2.5-2-OG
	蓝Blue	TU2.5-2-BU

配套附件Accessory		
盖板Cover Plate	颜色Colour	订货号Order NO.
盖板Cover Plate	灰Gray	TU2.5-2-GY-EA
	橙Orange	TU2.5-2-OG-EA

跨接件Jumper	
极数Poles No.	订货号Order NO.
2	TJA5.2-2
3	TJA5.2-3
4	TJA5.2-4
5	TJA5.2-5
6	TJA5.2-6
7	TJA5.2-7
8	TJA5.2-8
9	TJA5.2-9
10	TJA5.2-10
正面标记(小)Front Marker(Small)	订货号Order NO.
可提供印字服务Printing Service	TMB5.2-120
正面标记(大)Front Marker(Big)	订货号Order NO.
可提供印字服务Printing Service	305801

4mm² TU接线端子

TU Terminal Block

技术参数Technical Parameter		
厚度Thickness	宽度Width	高度Height
6.2	47.3	46.2
IEC	UL	
1000	600	
32	30	
刚性Solid	柔性Fine Stranded	带冷压头Furrule
0.2-6	0.2-4	0.2-4
26-10	26-10	26-10
M3		
0.5		
V0		
8-9		

订货信息Order Information	
订货号Order NO.	TU4-2-GY
TU4-2-OG	
TU4-2-BU	

配套附件Accessory	
订货号Order NO.	TU2.5-2-GY-EA
TU2.5-2-OG-EA	

订货号Order NO.	TJA6-2
TJA6-3	
TJA6-4	
TJA6-5	
TJA6-6	
TJA6-7	
TJA6-8	
TJA6-9	
TJA6-10	
订货号Order NO.	TMB6.2-100
订货号Order NO.	306801

6mm² TU接线端子

TU Terminal Block

技术参数Technical Parameter		
厚度Thickness	宽度Width	高度Height
8.2	47.3	46.2
IEC	UL	
1000	600	
41	50	
刚性Solid	柔性Fine Stranded	带冷压头Furrule
0.2-10	0.2-6	0.25-6
24-8	24-8	24-8
M4		
1.2		
V0		
9-10		

订货信息Order Information	
订货号Order NO.	TU6-2-GY
TU6-2-OG	
TU6-2-BU	

配套附件Accessory	
订货号Order NO.	TU2.5-2-GY-EA
TU2.5-2-OG-EA	

订货号Order NO.	TJA8.2-2
TJA8.2-3	
TJA8.2-4	
TJA8.2-5	
TJA8.2-6	
TJA8.2-7	
TJA8.2-8	
TJA8.2-9	
TJA8.2-10	
订货号Order NO.	TMB8.2-50
订货号Order NO.	308801

10mm² TU接线端子

TU Terminal Block

技术参数Technical Parameter		
厚度Thickness	宽度Width	高度Height
10.2	47.3	46.2
IEC	UL	
1000	600	
57	65	
刚性Solid	柔性Fine Stranded	带冷压头Furrule
0.5-16	0.5-10	0.5-10
20-6	20-6	20-6
M4		
1.2		
V0		
10-11		

订货信息Order Information	
订货号Order NO.	TU10-2-GY
TU10-2-OG	
TU10-2-BU	

配套附件Accessory	
订货号Order NO.	TU2.5-2-GY-EA
TU2.5-2-OG-EA	

订货号Order NO.	TJA10.2-2
*	
*	
*	
*	
*	
*	
*	
*	
*	
订货号Order NO.	TMB10.2-50
订货号Order NO.	310801

16mm² TU接线端子

Ground Terminal Block

技术参数Technical Parameter		
厚度Thickness	宽度Width	高度Height
12.2	52.8	54.35
IEC	UL	
1000	600	
76	85	
刚性Solid	柔性Fine Stranded	带冷压头Furrule
1.5-25	1.5-16	1.5-16
16-4	16-4	16-4
M5		
2.0		
V0		
13-14		

订货信息Order Information	
订货号Order NO.	TU16-2-GY
TU16-2-OG	
TU16-2-BU	

配套附件Accessory	
订货号Order NO.	TU16-2-GY-EA
TU16-2-OG-EA	

订货号Order NO.	*
*	
*	
*	
*	
*	
*	
*	
*	
订货号Order NO.	TMB10.2-50
订货号Order NO.	310801