



PR5-50A-035



技术参数(Technical Data)

间距(Center Space)	5.0x7.1mm
额定电流(Rated Current)	50A
压线螺钉(Screw)	M3.5-6H
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	10 lbf · in


PR5-60A-022



技术参数(Technical Data)

间距(Center Space)	2.4x9.0mm
额定电流(Rated Current)	60A
压线螺钉(Screw)	M4
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	14 lbf · in


PR5-60A-023



技术参数(Technical Data)

间距(Center Space)	6.0x9.0mm
额定电流(Rated Current)	60A
压线螺钉(Screw)	M4
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	14 lbf · in


PR5-60A-027



技术参数(Technical Data)

间距(Center Space)	6.0x9.0mm
额定电流(Rated Current)	60A
压线螺钉(Screw)	M4
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	14 lbf · in


PR5-60A-028



技术参数(Technical Data)

间距(Center Space)	6.0x9.0mm
额定电流(Rated Current)	60A
压线螺钉(Screw)	M4
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	14 lbf · in


PR5-60A-029



技术参数(Technical Data)

间距(Center Space)	6.0x9.0mm
额定电流(Rated Current)	60A
压线螺钉(Screw)	M4
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	14 lbf · in


PR5-60A-024



技术参数(Technical Data)

间距(Center Space)	6.0x9.0mm
额定电流(Rated Current)	60A
压线螺钉(Screw)	M4
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	14 lbf · in


PR5-60A-025



技术参数(Technical Data)

间距(Center Space)	6.0x9.0mm
额定电流(Rated Current)	60A
压线螺钉(Screw)	M4
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	14 lbf · in


PR5-60A-026



技术参数(Technical Data)

间距(Center Space)	6.0x9.0mm
额定电流(Rated Current)	60A
压线螺钉(Screw)	M4
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	14 lbf · in


PR5-60A-034



技术参数(Technical Data)

间距(Center Space)	5.2x9.8mm
额定电流(Rated Current)	60A
压线螺钉(Screw)	M4
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	14 lbf · in


PR5-60A-035



技术参数(Technical Data)

间距(Center Space)	5.0x10.1mm
额定电流(Rated Current)	60A
压线螺钉(Screw)	M4
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	14 lbf · in

PR5-60A-036



技术参数(Technical Data)

间距(Center Space)	5.0x10.1mm
额定电流(Rated Current)	60A
压线螺钉(Screw)	M4
焊接端子(Terminal Body)	Brass, Tin Plated
螺钉扭矩(Screw Torque)	14 lbf · in

QT 密封止焊型50A~300A
QT RIVETED GASKET STRAIGHT PIN

QT 密封止焊型50A~300A
QT RIVETED GASKET STRAIGHT PIN